SOLENOID OPERATED CARTRIDGE

CEES-010-SEFN

DIRECT OPERATED
SPOOL TYPE

ATLANTIC Fluid Tech



Dimensions: mm [inches]



SPECIFICATIONS

Max. operating pressure:	350 bar (5000 psi)
Max. operating pressure on port 1:	210 bar (3000 psi)
Rated flow:	10 l/min (3 gpm)
Cavity:	SAE-08-4N
Weight:	0,18 kg (0,40 lbs)
Min. voltage required:	90% of nominal
Coil type:	M7 or M3 type
Ambient temperature:	-20/+50 °C (-4/+122 °F)
Contamination class to ISO 4406:	See technical spec.
Seal kit:	RB700101
Installation torque:	45 - 50 Nm (33 - 37 ft-lb)
MTTFd:	150 years
Leakage:	120 cm³/min (@46 cSt) 7,3 in³/min (@46 cSt)

NOTES

OPTIONS

		
Standard	Push and pull manual override	Push pull and twist manual override

CURVES



ORDERING CODES

Quick code	Description	Options	
CE000029	CEES-010-SEFN-52-S08-N350	Standard	
CE000095	CEES-010-SEFL-52-S08-N350	Push and pull manual override	
CE000145	CEES-010-SEFG-52-S08-N350	Push pull and twist manual override	

Revision A1