





SOLENOID OPERATED CARTRIDGE

CEBN-080-NAFNPILOT OPERATED
POPPET TYPE**SPECIFICATIONS**

Max. operating pressure:	350/500 bar (5000/7200 psi)
Rated flow:	80 l/min (21 gpm)
Cavity:	SAE-10-2N
Weight:	0,18 kg (0,40 lbs)
Min. voltage required:	90% of nominal
Coil type:	M7 or M3 type
Ambient temperature:	-20/+50 °C (-4/+122 °F)
Contamination class to ISO 4406:	See technical spec.
Seal kit:	RB900082
Installation torque:	55 - 62 Nm (41 - 46 ft-lb)
MTTFd:	150 years

NOTES**OPTIONS****SEALING CAP**

Standard

Push style
overrideKnob style
overrideOrdering code:
AT000113**CURVES****ORDERING CODES**

Quick code	Description	Options	Max operating pressure	
CE000277	CEBN-080-NAFN-32-S10-N350	Standard	350 bar (5000 psi)	
CE000278	CEBN-080-NAFP-32-S10-N350	Push style override	350 bar (5000 psi)	
CE000279	CEBN-080-NAFK-32-S10-N350	Knob style override	350 bar (5000 psi)	
CE000577	CEBN-080-NAFN-32-S10-N500	Standard	500 bar (7200 psi)	
CE000578	CEBN-080-NAFP-32-S10-N500	Push style override	500 bar (7200 psi)	
CE000579	CEBN-080-NAFK-32-S10-N500	Knob style override	500 bar (7200 psi)	