



SOLENOID OPERATED CARTRIDGE

CEBN-310-NAFN

PILOT OPERATED
POPPET TYPE



SPECIFICATIONS

Max. operating pressure:	350/500 bar (5000/7200 psi)
Rated flow:	310 l/min (82 gpm)
Cavity:	SAE-16-2N
Weight:	0,36 kg (0,79 lbs)
Min. voltage required:	90% of nominal
Coil type:	M7 or M3 type
Ambient temperature:	-20/+50 °C (-4/+122 °F)
Contamination class to ISO 4406:	See technical spec.
Seal kit:	RA900084
Installation torque:	200 - 210 Nm (148 - 155 ft-lb)
MTF _d :	150 years

NOTES

OPTIONS

SEALING CAP


Standard



Push style
override




Knob style
override



Ordering code:
AT000113

CURVES



ORDERING CODES

Quick code	Description	Options	Max operating pressure	
CE000411	CEBN-310-NAFN-06-S16-N350	Standard	350 bar (5000 psi)	
CE000412	CEBN-310-NAFP-06-S16-N350	Push style override	350 bar (5000 psi)	
CE000413	CEBN-310-NAFK-06-S16-N350	Knob style override	350 bar (5000 psi)	
CE000711	CEBN-310-NAFN-06-S16-N500	Standard	500 bar (7200 psi)	
CE000712	CEBN-310-NAFP-06-S16-N500	Push style override	500 bar (7200 psi)	
CE000713	CEBN-310-NAFK-06-S16-N500	Knob style override	500 bar (7200 psi)	